


17, NOTE 4

BILL OF MATERIALS			
ITEM	QTY	PART NUMBER	DESCRIPTION
1	1	32-10-1-1-0037	LANDING GEAR, MAIN
2	2	32-10-1-1-0039	ATTACH BLOCK, LANDING GEAR
3	2	32-10-1-1-0119	RUBBER PAD, GEAR BLOCK
4	2	32-10-1-3-0101	LANDING GEAR REINFORCEMENT
5	2	32-10-1-1-0103	AXLE, MAIN LANDING GEAR
6	4	32-30-1-1-0104	SPACER
7	2	CLEVELAND 40-7813	WHEEL ASSEMBLY
8	2	CLEVELAND 30-9	BRAKE ASSEMBLY
9	4	AMC124A	BOLT
10	8	AMC11A	BOLT
11	8	AM4-23A	BOLT
12	16	AN365-428A	NUT
13	4	MS21042-5	NUT
14	8	AN660-516	WASHER
15	32	AN660-416	WASHER
16	4	AN823-30	ELBOW
17	6	BUNTING P/N 242-B	POP-IN BEARING
18	14FT	MIL-H-222576	STRATOFLUX 124-3 HOSE
19	4	MS27053	STRATOFLUX 851-3 STRAIGHT FITTING
20	2	MS21025-24	AXLE NUT
21	2	MS24665-360	CUTTER PIN
22	1	AMC16	BOLT



NOTE 3

NOTE 1

- NOTES:
- 1) SECURE BRAKE LINE TO LANDING GEAR LEG GROOVE WITH PERMATEX CLEAR RTV
  - 2) MATCH DRILL USING LANDING GEAR ATTACH BLOCK
  - 3) LOOP SUFFICIENT BRAKE LINE FOR PEDAL TRAVEL
  - 4) .375 IN. DIA HOLE FOR BRAKE LINE, (TYP) 1 IN. FROM EDGE OF PART.
  - 5) MATCH DRILL LANDING GEAR USING SPINDLE AS GUIDE, CENTERED FORD AND AFT ON SPINDLE PAD
  - 6) EFFECTIVITY: G-2026-222
  - 7) AN4-16, CUT TO 1.375 LONG, CHAMFER, BOND IN PLACE USING 6 PLIES BI-DIRECTIONAL GLASS 7725 [±45°], JEFFCO 1307/3153, 1.5" ALL SIDES.

0	C	..	CHANGE BRAKE LINE SPEC	8/26/97	MG
CHG.	REV.	ECH	DESCRIPTION OF CHANGE	DATE	BY
AkroTech					
DIMENSIONS AND TOLERANCES IN ACCORDANCE WITH ANST Y14.5M-1992					
THIRD ANGLE PROJECTION			DRAWING NO. 32-10-2-1-0101		
DIMENSIONS ARE IN INCHES			PART NO.		
SCALE: NONE			TITLE: LANDING GEAR ASSEMBLY		
UNSPECIFIED TOLERANCES			MATERIAL:		
ONE PLACE DEC. (X.X) ± 0.1					
TWO PLACE DEC. (X.XX) ± 0.01					
THREE PLACE DEC. (X.XXX) ± 0.001					
ANGLES					
DATE: 6/12/97		PAGE: 1 OF 1		DRAWN BY: DMK	
				APPROVED:	